V7 L22WD

Professional Line

The elegant design of the V7 L22WD and the superb specifications like 1680 x 1050 super Wide viewing Angle, integrated DVI-D Input, high contrast ratio of 700:1 and an excellent response time of 5 ms make the display perfect for office use as well as for home entertainment.

Specifications

Panel Size	22” (559 mm)
Aspect Ratio	16:10 (~ 474 x 296 mm)
Panel Specification	CMO Panel, TN
Recommended Resolution	1680 x 1050 Super Wide Viewing Angle
Colours max.	16.2 Mio
Brightness typ.	280 cd/m²
Contras Ratiot typ.	700:1
Viewing Angle H/V	170°/160°
Response Time typ.	5 (2/3) ms
Features	Speakers, Kensington® Security Port, internal power supply, silver-black design
Adjustment	Auto-Setup (Clock, Phase, H/V-Position) Brightness, Contrast Ratio, Sharpness, Color, OSD Position, Language, Audio, Recall etc.
Frequency at Resolution	640 x 480 @ 75 Hz 800 x 600 @ 75 Hz 1024 x 768 @ 75 Hz 1280 x 1024 @ 75 Hz 1440 x 900 @ 75 Hz 1680 x 1050 @ 60 Hz
Horizontal Frequency	30 - 82 kHz
Vertical Frequency	56 - 76 Hz
Video Bandwidth	140 Mhz
Input Signal	RGB analog and digital
Input Terminal	15pin D-Sub, 24 pin DVI-D
Plug & Play	DDC2B
Power Management	VESA DPMS, DVI DMPM, ENERGY STAR®
Power Consumption On/Off	48/1 Watt max.
Power Requirements	AC 100 - 240V, 50/60 Hz
DimensionsWxHxD **with stand** **without stand** **packaging**	 502 x 417 x 200 mm 502 x 365 x 60 mm 580 x 490 x 140 mm
Weight without/with stand **incl. packaging**	4.4 kg / 5 kg 6.5 kg
Tilt	0° - 20°
Storage/Operating Temperature	5-35°/-20-55°C, Humidity: 20-80/20-85%
Certifications & Standards	CE, TÜV/GS, TCO´03, ISO 13406-2
Supplied Accessories	12 language manual CD-Rom, quick start guide, power cable, VGA cable, audio cable
Pixel Criteria	bright <= 4, dark <= 4, total <= 9
Service	3 years on-site

The data in this publication is for illustration purposes only and does not necessarily represent standards or specifications which must be met by V7 Videoseven. Design and specifications are subject to change without prior notice. Trademarks belong to their respective owners. No responsibility assumed and all liability for damages resulting from use of this information or for any errors or omissions are disclaimed. Measurement standards and testing conditions as per manufacturer definitions, available on request.
Issue: 06/2006